


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Jefferson de Souza Marques

> **Empresa VSAT-ID** Link kbps **Plataforma EMC Brasil** VIVO-PER-31170089-MG 256k/128k **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

: 23 16APSK-9/10 (SNR threshold: 23.5 dB) Max MODCOD

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055828 DVB-S2 102 Yes 9.320000 12.055828 DVB-S2 4 No

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

: 12.055951 GHz Frequency Symbol Rate : 9.319837 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 15 8PSK-5/6

Pilot : On Frame length : Short DVB S2 Mode : ACM Roll off : 0.20 : 13.1 dB SNR : -25 dBm Input Power

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled IDU Output Power : -25 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 14.125500 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)
IDU Output Power : -24.2 dBm
ODU Output Power : 33.4 dBm
EIRP
EIRP
                   : 46.7 dBW
Es/No
                   : 12.0 dB
Header Compression : Disabled
Timing correction : -258 us (260617 us)
Frequency correction: 120 Hz
IP DVB 10.50.1.28/32
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=1550 ms
64 bytes from 8.8.8.8: time=920 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=770 ms
64 bytes from 8.8.8.8: time=900 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 770/1000/1550 ms
```