

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26038056-PE
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)

IDU Output Power : -20.1 dBm

Es/No : 13.0 dB Header Compression : Disabled

Timing correction : -191 us (260899 us)

Frequency correction: 100 Hz

```
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                              Name
Enable
         9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
           : On
: Forward link up
Rx State
              : 1326, GlobalIP@Telstar-14R
: 12.055945 GHz
: 9 310065
DVB State
Network
Frequency
Symbol Rate
S2 ModCod
  - receiving : 16 8PSK-8/9
     - current max : 16
                         8PSK-8/9
             : On
Pilot
Frame length : Short DVB S2 Mode : ACM
                  : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
                  : 13.0 dB
SNR
Input Power
                  : -35 dBm
# ping 8.8.8.8
Request timed out
64 bytes from 8.8.8.8: time=820 ms
64 bytes from 8.8.8.8: time=820 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=620 ms
--- ping statistics ---
5 packets transmitted, 4 received, 20.00 percent packet loss
rtt min/avg/max = 700/730/820 ms
```

