


Solicitante: PRODEMGE / SEE**NOC/Operadora:** Ermínio Junior**Operadora/Cliente:** Sergio Almeida**GRE/Prodemge:** João Antinossi**Responsável/cliente:** Heloide Jesus**Consórcio**
EMC/Vodanet**VSAT-ID**
SEE-BURO-22056**Porta kbps**
2Mbps**Plataforma**
VSAT**OBS: TESTE REALIZADO COM O TEMPO CHUVOSO(GAROA)**

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -13.8 dBm

ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Es/No : 14.5 dB
Header Compression : Disabled - HC for RCS2 not supported by HUB
Timing correction : -400 us (281855 us)
Frequency correction: 100 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	4.883300	12.176420	DVB-S2 104	0	0.0	E		Yes	
1	1	16.667000	11.962753	DVB-S2 2	0	0.0	E		Yes	

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 65281, Prodemge@Vodanet
Frequency : 12.176320 GHz
Symbol Rate : 4.882995 Msps
S2 ModCod
- receiving : 16 8PSK-8/9
- current max : 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 16.2 dB
Input Power : -35 dBm

device show

System Information:

Name : SEE-BURO-22056
Location : BURITIZEIRO
Contact :
System Up time : 0 days, 00:31:18
CPU Load : 13%
System time(UTC) : 16 October 2017 14:37:06
Broadcast Message : not set

HW:

Model : SatLink 2000
HW ID : 120033
Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:4a:b3

Satellite (DVB) : 00:20:0e:10:4a:b3

arp show

NetAddr	State	MacAddr	If
10.212.128.2	Dynamic	74:e6:e2:d4:e4:73	1

Pinging 10.212.128.1 with 32 bytes of data:

Reply from 10.212.128.1: bytes=32 time=589ms TTL=56
Reply from 10.212.128.1: bytes=32 time=554ms TTL=56
Reply from 10.212.128.1: bytes=32 time=567ms TTL=56
Reply from 10.212.128.1: bytes=32 time=573ms TTL=56
Reply from 10.212.128.1: bytes=32 time=566ms TTL=56
Reply from 10.212.128.1: bytes=32 time=574ms TTL=56
Reply from 10.212.128.1: bytes=32 time=559ms TTL=56
Reply from 10.212.128.1: bytes=32 time=565ms TTL=56
Reply from 10.212.128.1: bytes=32 time=556ms TTL=56
Reply from 10.212.128.1: bytes=32 time=561ms TTL=56

Ping statistics for 10.212.128.1:

Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 554ms, Maximum = 589ms, Average = 566ms

www.globo.com – ok

www.hotmail.com – ok

www.google.com – ok

www.educacao.mg.gov.br – ok

www.prodemge.gov.br - ok

Responsável pelo teste de navegação:

Nome: Heliode Jesus

Função: Diretor

Identidade: MASP 0378674