TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

**NOC/Operador:** Rogério Momi Frias

Cliente: VIVO

Empresa	VSAT-ID	Link kbps	Plataforma
EMC Brasil	VIVO-PER-31077925-MG	256/128	VSAT

Satellite (DVB) RX Configuration

Auto start   : Enabled
Max MODCOD   : 23   16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog   : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode   PopId   Enable
* 0 0   9.320000   12.055825 DVB-S2 4   Yes
  1 1   0.000000   0.000000   DVB-S2 2   Yes

Satellite (DVB) Receiver Status

Rx State   : On
DVB State   : Forward link up
Network   : 1326, GlobalIP@Telstar-14R
Frequency   : 12.055842 GHz
Symbol Rate   : 9.319945 Msps
S2 ModCod
    - receiving : 16   8PSK-8/9
    - current max : 23   16APSK-9/10
Pilot   : On
Frame length   : Short
DVB S2 Mode   : ACM
Roll off   : 0.25
SNR   : 14.7 dB
Input Power   : -26 dBm

```
Satellite (DVB) TX Configuration
-------------------------------
Auto start          : Enabled
IDU Output Power    : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power    : max
EIRP                : max
Default CW Frequency: 0.000000 GHz
ATM mode            : VC-Mux
Header Compression  : None


Satellite (DVB) Transmitter Status
-------------------------------
State               : On (TDMA)
IDU Output Power    : -22.4 dBm
ODU Output Power    : 34.4 dBm
EIRP                : 47.7 dBW
Eb/No               : 15.0 dB
Header Compression  : Disabled
Timing correction   : -255 us (262558 us)
Frequency correction: -260 Hz




ping 8.8.8.8
64 bytes from 8.8.8.8: time=670 ms
64 bytes from 8.8.8.8: time=730 ms
64 bytes from 8.8.8.8: time=520 ms
64 bytes from 8.8.8.8: time=590 ms
64 bytes from 8.8.8.8: time=570 ms

--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received,  0.00 percent packet loss
rtt min/avg/max = 520/610/730 ms
```