


## TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23192089-CE
 256k/128k
 VSAT



# dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -20 dBm

IDU Max Output Power: 0.0 dBm

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -19.8 dBm

Es/No : 12.5 dB

Header Compression : Disabled

Timing correction : -133 us (254255 us)

Frequency correction: 120 Hz

# dvb rx show

Satellite (DVB) RX Configuration \_\_\_\_\_\_

Auto start : Enabled

: 23 16APSK-9/10 : 15 minute Max Traffic MODCOD

RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E

Yes

## Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up Network : 1326, T14R Beam : 12.059148 GHz Frequency Symbol Rate : 15.000105 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 22 16APSK-8/9

: On Pilot. : Short Frame length DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 : 14.8 dB SNR : -35 dBm Input Power

