

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-24054461-RN
 256k/128k
 VSAT



dvb rx show

Satellite (DVB) RX Configuration
----Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 30.000000 12.050000 DVB-S2 102 0 0.0 E Yes

1 1 25.333333 12.050000 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050045 GHz
Symbol Rate : 29.999915 Msps

S2 ModCod

- receiving : 7 QPSK-3/4 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.5 dB
Input Power : -34 dBm

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -15.1 dBm
Es/No : 7.5 dB
Header Compression : Disabled

Timing correction : -123 us (250088 us)

Frequency correction: 140 Hz

