


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23094591-CE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -24 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125700 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

```
: On (TDMA)
State
IDU Output Power : -23.8 dBm ODU Output Power : 34.8 dBm
                      : 48.1 dBW
EIRP
                      : 14.5 dB
Es/No
Header Compression : Disabled
Timing correction : -295 us (260392 us)
Frequency correction: 110 Hz
# dvb rx show
Satellite (DVB) RX Configuration
_____
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
Rx State : On

DVB State : Forward link up

Network : 1326. Global IPC
                     : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055780 GHz
Symbol Rate : 9.319972 Msps
S2 ModCod
   - receiving : 14 8PSK-3/4
      - current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.20
SNR : 13.8 dB
Input Power : -21 dBm
IP DVB 10.50.1.17/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=630 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 540/570/630 ms
```