

TERMO DE ACEITE TÉCNICO


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

EmpresaVSAT-IDEMC BrasilVIVO-PER-23248696-CE

Link kbps 256/128

Plataforma VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State: On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055759 GHz Symbol Rate : 9.319976 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 23 16APSK-9/10

Pilot: On
Frame length: Short
DVB S2 Mode: ACM
Roll off: 0.25
SNR: 14.6 dB
Input Power: -19 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -25 dBm

IDU Max Output Power: 0.0 dBm ODU Output Power: 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 14.125850 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -27.3 dBm
ODU Output Power : 33.4 dBm

EIRP : 46.7 dBW Eb/No : 14.0 dB

Header Compression: Disabled Timing correction: -246 us (260920 us)

Frequency correction: -230 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=1980 ms 64 bytes from 8.8.8.8: time=870 ms 64 bytes from 8.8.8.8: time=960 ms 64 bytes from 8.8.8.8: time=880 ms 64 bytes from 8.8.8.8: time=920 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 870/1120/1980 ms