

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

> **Empresa VSAT-ID** Link kbps Plataforma **EMC** Brasil VIVO-PER-25029134-PB 256/128 **VSAT**



Satellite (DVB) RX Configuration

: Enabled Auto start

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

1 1 0.000000 0.000000 DVB-S2 2 No

Satellite (DVB) Receiver Status

-----Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

: 12.055646 GHz Frequency

Symbol Rate : 9.319928 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On Frame length : Short DVB S2 Mode : ACM : 0.25 Roll off : 14.9 dB SNR Input Power : -27 dBm

```
Satellite (DVB) TX Configuration
Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.4 dBm
EIRP
         : 47.7 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression: None
Satellite (DVB) Transmitter Status
State : On (TDMA)
IDU Output Power : -22.5 dBm
ODU Output Power : 34.2 dBm
EIRP
         : 47.5 dBW
Eb/No
             : 14.0 dB
Header Compression: Disabled
Timing correction: -251 us (261294 us)
Frequency correction: -140 Hz
Pinging 10.53.0.243 with 32 bytes of data:
Reply from 10.53.0.243: bytes=32 time=2039ms TTL=61
Reply from 10.53.0.243: bytes=32 time=923ms TTL=61
Reply from 10.53.0.243: bytes=32 time=843ms TTL=61
Reply from 10.53.0.243: bytes=32 time=764ms TTL=61
Ping statistics for 10.53.0.243:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 764ms, Maximum = 2039ms, Average = 1142ms
Pinging 10.29.5.65 with 32 bytes of data:
Reply from 10.29.5.65: bytes=32 time=1881ms TTL=61
Reply from 10.29.5.65: bytes=32 time=1290ms TTL=61
Reply from 10.29.5.65: bytes=32 time=1847ms TTL=61
Reply from 10.29.5.65: bytes=32 time=922ms TTL=61
Ping statistics for 10.29.5.65:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 922ms, Maximum = 1881ms, Average = 1485ms
ping 8.8.8.8
64 bytes from 8.8.8.8: time=2690 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=1290 ms
```

64 bytes from 8.8.8.8: time=910 ms 64 bytes from 8.8.8.8: time=900 ms

rtt min/avg/max = 900/1340/2690 ms

5 packets transmitted, 5 received, 0.00 percent packet loss

--- 8.8.8.8 ping statistics ---