


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31346225-MG
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -19.9 dBm
Es/No : 10.0 dB
Header Compression : Disabled

Timing correction : 45 us (248457 us)

Frequency correction: -20 Hz

dvb rx show

Satellite (DVB) RX Configuration
----Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable 30.000000 11.592000 DVB-S2 102 * 0 0 0 0.0 E Yes 11.592000 DVB-S2 4 1 1 25.333000 0 0.0 E Yes Satellite (DVB) Receiver Status ______ Rx State : On : Forward link up DVB State : 1326, T14R Beam Network : 11.591904 GHz Frequency : 29.999551 Msps Symbol Rate S2 ModCod - receiving : 18 16APSK-2/3 16APSK-5/6 - current max : 21 Pilot : On Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 : 14.1 dB SNR Input Power : -33 dBm C:\Windows\svstem32\cmd.exe 🖺 SatLink VSAT 💢 ← → C ① 10.29.73.137/wmi/dwp/index_page.dwp o-- ☆ : 🔛 Apps 🖺 Sites Sugeridos 📙 Importado do IE 🚾 Qualp - Cálculo de ĸ 📙 API GOOGLE MAPS SatLink VSAT Status Device Status Satellite Model SatLink 2000 Statistics 16.0.1.57 Software Version Device LAN MAC Address 00:20:0e:10:54:c2 DHCP DVB MAC Address 00:20:0e:10:54:c2 Eventlog System Up Time 0 days, 00:36:09 Satellite CPU Load 28% VIVO-PER-31346225-MG System Name Static NAT System Contact Lineup Device System Location São Romao - MG tatísticas do Ping para 8.8.8.8: Pacotes: Enviados = 41, Recebidos = 41, Perdidos = 0 (0% de perda). Help Introduction perna), oximar um número redondo de vezes em milissegundos: Mínimo = 504ms, Máximo = 2129ms, Média = 716ms rrol-C Status Configuration ` \Users\FenixSat>arp -a

0 🗹

w

C:\Users\FenixSat>

You are logged in as install (2) © Copyright 2006-2014 STM Group. All Rights Reserved.

· 😼 🔒 🖫 🐠