



## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-23083131-CE256/128VSAT





```
# dvb tx show
Satellite (DVB) TX Configuration
______
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 36.1 dBm
EIRP
                   : 47.0 dBW
Default CW Frequency: 14.125750 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (DVB-RCS)
IDU Output Power : -18.4 dBm
ODU Output Power : 35.4 dBm
EIRP
                    : 46.3 dBW
Es/No
                    : 12.5 dB
Header Compression : Disabled
Timing correction : -100 us (261213 us)
Frequency correction: -50 Hz
# dvb rx show
Satellite (DVB) RX Configuration
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                                 Name
Enable
* 0 0
                    12.055825 DVB-S2 102 0 0.0 E
          9.320000
Yes
Satellite (DVB) Receiver Status
_____
Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
               : 12.055945 GHz
: 9.320195 Msps
Frequency
Symbol Rate
S2 ModCod
    - receiving : 15 8PSK-5/6
     - current max : 16 8PSK-8/9
Pilot : On
Frame length : Sho:
DVB S2 Mode : ACM
                   : Short
DVB S2 Stream type : MPEG-TS
Roll off
                   : 0.20
SNR
                   : 13.2 dB
Input Power : -29 dBm
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=820 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=570 ms
--- ping statistics ---
5 packets transmitted, 3 received, 40.00 percent packet loss
rtt min/avg/max = 560/610/720 ms
```

