


## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Jefferson de Souza Marques Cliente: VIVO

> **Empresa VSAT-ID** Link kbps **Plataforma EMC Brasil** VIVO-PER-25025929-PB 256/128 **VSAT**



Satellite (DVB) RX Configuration \_\_\_\_\_ : Enabled Auto start

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable 9.320000 12.055825 DVB-S2 4 \* 0 0 Yes

Satellite (DVB) Receiver Status \_\_\_\_\_

Rx State : On

: Forward link up DVB State

Network

: 1326, GlobalIP@Telstar-14R : 12.055640 GHz : 9.319908 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 23 16APSK-9/10

: On Pilot Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 : 14.0 dB SNR : -21 dBm Input Power

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled IDU Output Power : -25 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 14.125500 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)
IDU Output Power : -23.6 dBm
ODU Output Power : 33.8 dBm
EIRP
EIRP
                   : 47.1 dBW
Eb/No
                   : 15.0 dB
Header Compression : Disabled
Timing correction : -216 us (261499 us)
Frequency correction: -250 Hz
IP DVB 10.50.0.23/32
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=1550 ms
64 bytes from 8.8.8.8: time=920 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=770 ms
64 bytes from 8.8.8.8: time=900 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 770/1000/1550 ms
```