

TERMO DE ACEITE TÉCNICO


Solicitante: PRODEMGE / SEE

NOC/Operadora: Hernan Alves **Operadora/Cliente: Ederson Martins**

GRE/Prodemge: João Antinossi Responsável/cliente: Evandro Alves de Almeida

> Consórcio **VSAT-ID** Porta kbps Plataforma EMC/Vodanet SEE-SACO-22232 2Mbps **VSAT**

> > Port eth0 on SEE-SACO-22232 (10.213.31.1)



PRTG Traffic Grapher V6.2.0.907 - 19/10/2017 22:50:44

Satellite (DVB) RX Configuration Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

4.883300 12.176420 DVB-S2 104 0 0.0 E * 0 0

Yes

Satellite (DVB) Receiver Status

Rx State : On

: Forward link up DVB State

: 65281, Prodemge@Vodanet Network

: 12.176410 GHz : 4.882979 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 20 16APSK-4/5 - current max : 21 16APSK-5/6

Pilot : On Frame length : Shor DVB S2 Mode : ACM : Short DVB S2 Stream type : MPEG-TS Roll off : 0.20 : 16.0 dB SNR Input Power : -39 dBm

```
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
                    : 46.5 dBW
EIRP
Default CW Frequency: 0.000000 GHz
                    : VC-Mux
ATM mode
Header Compression : UDP/IP
Satellite (DVB) Transmitter Status
_____
                    : On (DVB-RCS2)
State
IDU Output Power : -14.6 dBm
ODU Output Power : 33.3 dBm
EIRP
                    : 46.6 dBW
Es/No
                    : 14.0 dB
\hbox{{\tt Header Compression}} \quad \hbox{: Disabled} \quad \hbox{{\tt - HC for RCS2 not supported by HUB}}
Timing correction : -242 us (281676 us)
Frequency correction: 30 Hz
System Information:
   Name
                        : SEE-SACO-22232
    Location
                        : SO FRANCISCO/MG
    Contact
    System Up time : 0 days, 00:23:45 CPU Load : 10%
                       : 19 October 2017 21:21:15
    System time(UTC)
    Broadcast Message : not set
HW:
                        : SatLink 2000
    Model
                        : 120033
    HW ID
    Main board ID
                       : 120026 R6.2
MAC addresses:
    Ethernet (LAN) : 00:20:0e:10:4c:ac Satellite (DVB) : 00:20:0e:10:4c:ac
   Ethernet (LAN)
# arp show
  NetAddr
                State MacAddr
   10.213.31.2 Dynamic 1c:39:47:5b:e2:48 1
C:\ >ping -t 10.213.31.1
Pinging 10.213.31.1 with 32 bytes of data:
Reply from 10.213.31.1: bytes=32 time=547ms TTL=56
Reply from 10.213.31.1: bytes=32 time=580ms TTL=56
Reply from 10.213.31.1: bytes=32 time=563ms TTL=56
Reply from 10.213.31.1: bytes=32 time=534ms TTL=56
Reply from 10.213.31.1: bytes=32 time=541ms TTL=56
Reply from 10.213.31.1: bytes=32 time=566ms TTL=56
Reply from 10.213.31.1: bytes=32 time=548ms TTL=56
Reply from 10.213.31.1: bytes=32 time=562ms TTL=56
Reply from 10.213.31.1: bytes=32 time=543ms TTL=56
Reply from 10.213.31.1: bytes=32 time=567ms TTL=56
Reply from 10.213.31.1: bytes=32 time=561ms TTL=56
```

Reply from 10.213.31.1: bytes=32 time=539ms TTL=56

```
Reply from 10.213.31.1: bytes=32 time=567ms TTL=56

Ping statistics for 10.213.31.1:

Packets: Sent = 13, Received = 13, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 534ms, Maximum = 580ms, Average = 555ms
```

Lista de sites acessados:

www.globo.com - ok www.yahoo.com - ok www.hotmail.com - ok www.google.com - ok www.educacao.mg.gov.br - ok www.prodemge.gov.br - ok

Responsável pelo teste de navegação: Nome: Evandro Alves de Almeida

Função: Vice-Diretor MASP: 10743763