


TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Wallace Teixeira Operadora/Cliente: Eduardo Tadra

Responsável/cliente: Vanusa de cassia gualberto GRE/Prodemge: João Antinossi

Consórcio VSAT-ID Plataforma Porta kbps EMC/Vodanet SEE-BRAS-22593 2MBPS **VSAT**



PRTG Traffic Grapher V6.2.0.907 - 9/11/2017 00:37:16

dvb rx show

Satellite (DVB) RX Configuration : Enabled Auto start

Auto start . _____ Max Traffic MODCOD : 23 16APSK-9/10 RX watchdoq : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 4.883300 12.176420 DVB-S2 104 0 0.0 E

Yes

11.962753 DVB-S2 2 0 0.0 E 1 16.667000

Yes

Satellite (DVB) Receiver Status

Rx State

DVB State

: On: Forward link up: 65281, Prodemge@Vodanet

. volume 12.177039 GHz
Symbol Rate : 4.882007

- receiving : 4 QPSK-1/2 - current max : 21 16APSK-5/6

Pilot : On : Short Frame length

```
DVB S2 Mode
                    : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR
                    : 16.6 dB
Input Power
                    : -31 dBm
# dvb tx show
Satellite (DVB) TX Configuration
-----
Auto start
                    : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm EIRP : 46.5 dBW
EIRP
                    : 46.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP
Satellite (DVB) Transmitter Status
_____
State : On (DVB-RCS2)
IDU Output Power : -19.7 dBm
ODU Output Power : 34.0 dBm
EIRP
                    : 47.3 dBW
                    : 13.5 dB
Es/No
\hbox{{\tt Header Compression}} \quad \hbox{{\tt :}} \quad \hbox{{\tt Disabled}} \quad \hbox{{\tt - HC for RCS2 not supported by HUB}}
Timing correction : -121 us (281420 us)
Frequency correction: -90 Hz
# device show
System Information:
            : SEE-BRAS-22593
   Name
    Location
                        : Braúnas - MG
    Contact
    System Up time : 0 days, 04:21:41

CPU Load : 6%

System time(UTC) : 09 November 2017 03:07:11
    Broadcast Message : not set
HW:
    Model
                        : SatLink 2000
    HW ID
                        : 120033
    Main board ID
                        : 120026 R6.2
MAC addresses:
   Ethernet (LAN) : 00:20:0e:10:58:ba
Satellite (DVB) : 00:20:0e:10:58:ba
# arp show
   NetAddr State MacAddr
                                             Ιf
Pinging 10.214.184.1 with 32 bytes of data:
Reply from 10.214.184.1: bytes=32 time=559ms TTL=56
Reply from 10.214.184.1: bytes=32 time=593ms TTL=56
Reply from 10.214.184.1: bytes=32 time=564ms TTL=56
Reply from 10.214.184.1: bytes=32 time=539ms TTL=56
Reply from 10.214.184.1: bytes=32 time=619ms TTL=56
Reply from 10.214.184.1: bytes=32 time=568ms TTL=56
Reply from 10.214.184.1: bytes=32 time=575ms TTL=56
Reply from 10.214.184.1: bytes=32 time=572ms TTL=56
Reply from 10.214.184.1: bytes=32 time=574ms TTL=56
Reply from 10.214.184.1: bytes=32 time=537ms TTL=56
Reply from 10.214.184.1: bytes=32 time=716ms TTL=56
```

```
Reply from 10.214.184.1: bytes=32 time=554ms TTL=56
Reply from 10.214.184.1: bytes=32 time=660ms TTL=56
Ping statistics for 10.214.184.1:
    Packets: Sent = 13, Received = 13, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 537ms, Maximum = 716ms, Average = 586ms
Lista de sites acessados:
www.globo.com - ok
www.yahoo.com - ok
www.hotmail.com - ok
<u>www.google.com</u> – ok
www.educacao.mg.gov.br - ok
www.prodemge.gov.br - ok
Responsável pelo teste de navegação:
Nome: Vanusa de cassia gualberto farias
Função: Diretora
Identidade: MASP: 1069929-9
```