


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-23091800-CE256/128VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode Popld SatId Pos SatName Name Enable

* 0 0 9.320000 12.055825 DVB-S2 4 0 0.0 E Yes

Satellite (DVB) Receiver Status

.....

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055977 GHz Symbol Rate : 9.320152 Msps

S2 ModCod

receiving : 14 8PSK-3/4current max : 16 8PSK-8/9

Pilot : On

Frame length : Short

DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 12.8 dB Input Power : -28 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -22 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.6 dBm

EIRP : 45.5 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -22.0 dBm
ODU Output Power : 34.8 dBm

EIRP : 45.7 dBW Es/No : 11.0 dB

Header Compression: Disabled Timing correction: -243 us (260337 us)

Frequency correction: -30 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=620 ms 64 bytes from 8.8.8.8: time=720 ms 64 bytes from 8.8.8.8: time=730 ms 64 bytes from 8.8.8.8: time=700 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 620/690/730 ms