


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Cliente: VIVO

> Empresa VSAT-ID Link kbps Plataforma EMC Brasil VIVO-PER-22004432-PI 256k/128k **VSAT**



dvb tx show

Satellite (DVB) TX Configuration

: Enabled Auto start IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm

Default CW Frequency: 14.162500 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

: On (DVB-RCS)
IDU Output Power : -20.2 dBm
Es/No : 14.5 dB Es/No Header Compression : Disabled

Timing correction : -380 us (259806 us)

Frequency correction: -90 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

```
Yes
 Satellite (DVB) Receiver Status
Rx State : On
DVB State : Forward link up
                                                                                                               : 1326, T14R Beam
 Network
 Frequency : 12.055939 GHz
Symbol Rate : 9.320132 Msps
 S2 ModCod
                                                                                                           : 15 8PSK-5/6
                receiving
                             - current max : 16 8PSK-8/9
 Pilot
                                                                                                               : On
Frame length
                                                                                                               : Short
                                                                                                                   : ACM
  DVB S2 Stream type : MPEG-TS
                                                                                                         : 0.20
  Roll off
                                                                                                              : 14.7 dB
  SNR
                                                                                                              : -29 dBm
  Input Power
Responta de 8.9.8.8: byte Responta de 8.9.8.3: byte Responta de 8.9.8.
                                                                                                                                                                                               _ 0 X
          tatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 162, Recebidos = 162, Perdidos = 0 (0% de
            acosta: Enviados = 152, Recebidos = 162, Perdidos
oxinar um número redondo de vezes en milissegundos:
Mínino = 521ms, Máxino = 1863ms, Média = 797ms
trol-C
         .
∖Windows\System32>ARP -A
         \Windows\System32>UIUO-PER 22004432-PI E.M JOSÉ SALES DIAS - ESPERANTINA-PI
```

0 0.0 E

* 0 0 9.320000 12.055825 DVB-S2 102