


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31076929-MG
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -23 dBm IDU Max Output Power: 0.0 dBm

```
ODU Output Power : 33.7 dBm EIRP : 47.0 dBW
Default CW Frequency: 14.125750 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
______
: On (TDMA)

IDU Output Power : -21.8 dBm

ODU Output Power : 33.6 dBm

EIRP
State
                    : On (TDMA)
EIRP
                     : 46.9 dBW
                     : 14.0 dB
Es/No
Header Compression : Disabled
Timing correction : -31 us (262572 us)
Frequency correction: -370 Hz
# dvb rx show
Satellite (DVB) RX Configuration
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
                    : 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055691 GHz

Symbol Rate : 9.319976 Msps
S2 ModCod
   - receiving : 1 QPSK-1/4
     - current max : 15 8PSK-5/6
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Mode
Roll off
                    : 0.20
SNR
                    : 14.3 dB
Input Power : -26 dBm
IP DVB 10.53.0.63/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=810 ms
64 bytes from 8.8.8.8: time=890 ms
64 bytes from 8.8.8.8: time=770 ms
64 bytes from 8.8.8.8: time=840 ms
64 bytes from 8.8.8.8: time=900 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 770/840/900 ms
```

#		
π		