

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-24052361-RN

Link kbps
256k/128k

Plataforma
VSAT



SatLink VSAT

10.29.64.89/wmi/dwsp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:55:3d

00:20:0e:10:55:3d

0 days, 00:07:37

31%

VIVO-PER-24052361-RN

CEARA MIRIM/RN

104804040203090202580000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

Termin 10/29/64/89

Ln/No : 4,5 dB

Header Compression : Disabled

Timing correction : -27 us (251047 us)

Frequency correction : -150 Hz

Satellite (DVB) TX Configuration

Auto start : Enabled

120 Output Power : -20 dBm

120 Max Output Power : 0.0 dBm

ODU Output Power : 32.0 dBm

ERP : 46.0 dBm

Default CF Frequency : 0.000000 GHz

RTN mode : 0G-Plus

Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-BCS2)

120 Output Power : -19.9 dBm

ODU Output Power : 32.1 dBm

ERP : 46.1 dBm

Ln/No : 11.5 dB

Header Compression : Disabled

Timing correction : -27 us (251047 us)

Frequency correction : -150 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic M02C0B : 23 16APRX-9/10

RX watchdog : 15 minutes

Idx Pri SymbRate(Mbps) Freq(GHz) Mode PopId SatId Pos SatName

W 0 0 25.333333 12.050000 DVB-S2 182 0 0.0 E

Satellite (DVB) Receiver Status

Rx State : On

ODU State : Forward link up

Watermark : 1320, T14B Beam

Frequency : 12.050194 GHz

Symbol Rate : 25.333310 Mbps

Q2 ModCod : - receiving : 14 8PRX-3/4

- current max : 22 16APRX-8/9

Pilot : On

Frame length : Short

ODU 22 Mode : 8PSK

ODU 22 Stream type : MPEG-TS

Roll off : 0.30

SNR : 15.6 dB

Input Power : -29 dBm

SatLink VSAT

10.29.64.89/wmi/dwsp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:55:3d

00:20:0e:10:55:3d

0 days, 00:07:37

31%

VIVO-PER-24052361-RN

CEARA MIRIM/RN

104804040203090202580000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atahio

Resposta de 0.0.0.0: bytes=32 tempo=550ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=742ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=810ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1272ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=779ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=844ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1265ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=713ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=821ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=881ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=724ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=764ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=870ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=742ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1552ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=845ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1154ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=718ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=792ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1188ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=714ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1156ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1065ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1089ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1445ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1546ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=767ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1897ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=1385ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=912ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=980ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=731ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=815ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=675ms TTL=44

Resposta de 0.0.0.0: bytes=32 tempo=854ms TTL=44

Estadísticas de Ping para 0.0.0.0:

Pacotes: Enviados = 47, Recibidos = 47, Perdidos = 0 Gb de

perda>

Aproximar un número redondea de veces en millasegundos:

Mínimo = 607ms, Máximo = 1814ms, Média = 955ms

Control-C

C:\Windows\System32>arp -a

Interface: 10.29.64.70 --- 0x0

Endereço IP Endereço físico Tipo

10.29.64.89 00-20-0e-10-55-3d dinâmico

10.29.64.95 ff-ff-ff-ff-ff-ff estático

224.0.0.2 01-00-5e-00-00-02 estático

224.0.0.22 01-00-5e-00-00-16 estático

224.0.0.251 01-00-5e-00-00-1b estático

224.0.0.252 01-00-5e-00-00-1c estático

239.252.255.258 01-00-5e-7f-ff-ff estático

255.255.255.255 ff-ff-ff-ff-ff-ff estático

C:\Windows\System32>