

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: Vivo

Empresa
EMC Brasil
VIVO-PER-25077821-PB

Link kbps
256K/128K
VSAT



dvb tx show

## Satellite (DVB) TX Configuration

-----

Auto start : Enabled

IDU Output Power : -13 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS2)

IDU Output Power : -13.9 dBm ODU Output Power : 32.8 dBm

EIRP : 46.1 dBW Es/No : 13.5 dB Header Compression : Disabled

Timing correction : -67 us (251052 us)

Frequency correction: -140 Hz

# dvb rx show

Satellite (DVB) RX Configuration \_\_\_\_\_

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable \* 0 0 25.333333 12.050000 DVB-S2 102 0 0.0 E Yes 1 1 30.000000 12.050000 DVB-S2 102 0 0.0 E Yes

## Satellite (DVB) Receiver Status

\_\_\_\_\_

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.049646 GHz
Symbol Rate : 25.332958 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 20 16APSK-4/5

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.1 : 14.1 dB Input Power : -28 dBm

```
Resporta de 8.8.8.8: bytes=32 tempo=888ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=655ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=577ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=579ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=685ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=685ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=685ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=947ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=735ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=735ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=735ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=781ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=2480ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=2480ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1823ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1823ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1823ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1825ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1825ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1825ms ITL=44
Resporta de 8.8.8.8: bytes=32 tempo=1875ms ITL=44
Resporta de 8.8.8.8:
```