

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-31083623-MG

Link kbps
256K/128K

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```

Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.5 dBm
EIRP                 : 46.5 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
  
```

Satellite (DVB) Transmitter Status

```

State                : On (DVB-RCS2)
IDU Output Power     : -15.8 dBm
ODU Output Power     : 32.5 dBm
EIRP                 : 45.5 dBW
  
```

Es/No : 11.5 dB
Header Compression : Disabled
dvb rx show
Timing correction : 55 us (250268 us)
Frequency correction: 120 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
1	1	30.000000	12.050000	DVB-S2	4	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050257 GHz
Symbol Rate : 25.333083 Msps
S2 ModCod
- receiving : 13 8PSK-2/3
- current max : 15 8PSK-5/6
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 10.7 dB
Input Power : -29 dBm

SatLink VSAT

10.29.65.73/wmi/dwp/index_page.dwp

Apps Sites Sugeridos uu4uç~'x Device



Status

Satellite
Statistics
Device
DHCP
Eventlog
Configuration
Satellite
IP
Static NAT
Lineup
Device
Help
Introduction
Status
Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:4c:c8
DVB MAC Address	00:20:0e:10:4c:c8
System Up Time	0 days, 01:13:21
CPU Load	15%
System Name	VIVO-PER-31083623-MG
System Contact	
System Location	Bocaiuva - MG
ODU Serial Number	104804040203090308970000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

Administrador: Prompt de Comando

Microsoft Windows [versão 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. Todos os direitos reservados.

C:\Users\Asus>ping 8.8.8.8 -t

Disparando 8.8.8.8 com 32 bytes de dados: TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=2173ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1191ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=2314ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1284ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1024ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1202ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1084ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1073ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1060ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=853ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=927ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1011ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=837ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=796ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=878ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=953ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1239ms TTL=49

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 17, Recebidos = 17, Perdidos = 0 (0% de perda).

Aproximar um número redondo de vezes em milissegundos:
Mínimo = 796ms, Máximo = 2314ms, Média = 1217ms

Control-C
^C

C:\Users\Asus>arp -a

Interface: 10.29.65.74 --- Bxc

Endereço IP	Endereço físico	Tipo
10.29.65.73	00-20-0e-10-4c-c8	dinâmico
10.29.65.79	ff-ff-ff-ff-ff-ff	estático
224.0.0.2	01-00-5e-00-00-02	estático
224.0.0.22	01-00-5e-00-00-16	estático
224.0.0.251	01-00-5e-00-00-fb	estático
224.0.0.252	01-00-5e-00-00-fc	estático
239.255.255.250	01-00-5e-7f-ff-fa	estático
255.255.255.255	ff-ff-ff-ff-ff-ff	estático

C:\Users\Asus>31083623_

PT 17:02 10/12/2017