

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-31330752-MG

Link kbps
256k/128k

Plataforma
VSAT



Browser: Google Chrome | URL: 10.29.37.33/ven/0wp/index_page.php

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:60:8e
DVB MAC Address	00:20:0e:10:60:8e
System Up Time	0 days, 00:06:55
CPU Load	11%
System Name	VIVO-PER-31330752-MG
System Contact	
System Location	Campanha - MG
COU Serial Number	104804040203090702750000
COU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved

Satellite (DVB) Transmitter Status

State : On (DVB-BCS2)

IDU Output Power : -10.1 dBm

OSU Output Power : 45.7 dBm

ERP : 11.0 dB

Header Compression : Disabled

Timing correction : -110 us (255412 us)

Frequency correction : -70 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx	Pri	SymbRate(Mbps)	Freq(GHz)	Mode	PupId	SatId	Poz	SatName
0	0	15.000000	12.059800	DVB-S2 102	0	0.0	E	

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.059828 GHz

Symbol Rate : 14.999939 Mbps

S2 ModCod : 19 16APSK-3/4

Pilot : On

Frame length : Short

DVB S2 Mode : QAM

DVB S2 Stream type : MPEG-TS

Roll off : 0.20

SNR : 13.0 dB

Input Power : -30 dBm

Browser: Google Chrome | URL: 10.29.37.33/ven/0wp/index_page.php

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:60:8e
DVB MAC Address	00:20:0e:10:60:8e
System Up Time	0 days, 14:18:14
CPU Load	15%
System Name	VIVO-PER-31330752-MG
System Contact	
System Location	Campanha - MG
COU Serial Number	104804040203090702750000
COU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved

Statistics

Resposta de 8.8.8.8: bytes=32 tempo=637ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2061ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1438ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=952ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1894ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2272ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2238ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2382ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1538ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=588ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=278ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=818ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=847ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=568ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2094ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=717ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=818ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1954ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2046ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1075ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=308ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=618ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=692ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=757ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=832ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=571ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=633ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=725ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=777ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=511ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=598ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=569ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=757ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=835ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=547ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2359ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1696ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=526ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=1687ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=2109ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=844ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=566ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=658ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=728ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=810ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=529ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=680ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=694ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=635ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=837ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=559ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=641ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=713ns TTL=55

Resposta de 8.8.8.8: bytes=32 tempo=793ns TTL=55

Estatísticas de Ping para 8.8.8.8:

Pacotes: Enviados = 63, Recebidos = 63, Perdidos = 0 (0% de perda).

#proximar um número redondo de vezes em milissegundos:

Mínimo = 511ns, Máximo = 2877ns, Média = 1012ns

Control-C

C:\Documents and Settings\Administrador>