


## **TERMO DE ACEITE TÉCNICO**

Solicitante: EMC

NOC/Operador: Jefferson de Souza Marques Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31360570-CE
 256k/128k
 VSAT



## Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

## Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.058791 GHz
Symbol Rate : 14.999941 Msps
S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 18 16APSK-2/3

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 12.1 dB
Input Power : -25 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start
                           : Enabled
IDU Output Power : -23 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                            : 47.0 dBW
EIRP
Default CW Frequency: 14.125500 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
State
                          : On (DVB-RCS2)
IDU Output Power
                         : -18.2 dBm
                          : 33.7 dBm
ODU Output Power
EIRP
                           : 47.0 dBW
Es/No
                            : 15.0 dB
Header Compression : Disabled
Timing correction : -45 us (255462 us)
Frequency correction: 120 Hz
                                                                                                                             _
  SatLink VSAT
                                                                                                                                     =
 ( ) 10.29.37.185/wmi/dwp/index_page.dwp
 혿 Mais visitados 🔞 Primeiros passos 🕒 WhatsApp 📝 Galeria do Web Slice 🚺 Sites Sugeridos 🔯 PGME
              SatLink VSAT
 Status
              Device Status
 Satellite
              Model
                            SatLink 2000
 Statistics
              Software Version
                            16.0.1.57
 Device
 DHCP
              LAN MAC Address
                           00:20:0e:10:5f:00
 Eventlog
              DVB MAC Address 00:20:0e:10:5f:00
 Configuration
              System Up Time
                            0 days, 00:10:52
 Satellite
             CPU Load
                            23%
 Static NAT
              System Name
                            VIVO-PER-31360570-CE
 Lineup
              System Contact
 Device
              System Location
                            São Tomé das Letras - MG
 Help
             ODU Serial Number 104804040203090402550000
 Introduction
 Status
              ODU HW Version 4.2
 Configuration
                                                             Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 439, Recebidos = 439, Perdidos = 0 (0% de perda),
Proximar un número redondo de vezes em milissegundos:
Minimo = 509ms, Máximo = 3263ms, Média = 940ms
Control-C
                             You are logged in as install (2)
                       © Copyright 2006-2014 STM Group. All Rights Rese
                                                            C:\Documents and Settings\Administrador>
                                                                                                                       terça-feira, 23 de maio de 2017

« 🐉 😋 🞝 🔼 13:39
```