

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Renan Borges Sousa

> **Empresa** VSAT-ID Link kbps Plataforma EMC Brasil VIVO-PER-31028118-MG 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

: 23 16APSK-9/10 (SNR threshold: 23.5 dB) Max MODCOD

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes 0.000000 0.000000 DVB-S2 2 Nο

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

: 12.055992 GHz Frequency Symbol Rate : 9.320079 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 23 16APSK-9/10

Pilot : On Frame length : Short DVB S2 Mode : ACM Roll off : 0.25

```
: 14.4 dB
SNR
                    : -28 dBm
Input Power
Satellite (DVB) TX Configuration
-----
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm EIRP : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -22.8 dBm

ODU Output Power : 33.5 dBm
EIRP
Eb/No
                     : 46.8 dBW
                     : 15.0 dB
Header Compression : Disabled
Timing correction : -210 us (261658 us)
Frequency correction: -230 Hz
IP DVB 10.53.0.195/32
#ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=1120 ms
64 bytes from 8.8.8.8: time=930 ms
64 bytes from 8.8.8.8: time=920 ms
64 bytes from 8.8.8.8: time=930 ms
64 bytes from 8.8.8.8: time=810 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 810/940/1120 ms
```