

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23189118-CE
 256k/128k
 VSAT



dvb tx show

#

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 35.6 dBm
EIRP : 46.5 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -21.7 dBm
ODU Output Power : 35.6 dBm
EIRP : 46.5 dBW
Es/No : 12.5 dB
Header Compression : Disabled

Timing correction : -201 us (260457 us)

Frequency correction: 10 Hz

#

```
# dvb rx show
Satellite (DVB) RX Configuration
______
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
Name
         Enable
                      12.055825 DVB-S2 102 0 0.0 E
         9.320000
* 0 0
Satellite (DVB) Receiver Status
Rx State
                  : On
                : Forward link up
DVB State
Network
                  : 1326, GlobalIP@Telstar-14R
Frequency
                 : 12.055877 GHz
                 : 9.319920 Msps
Symbol Rate
S2 ModCod
  - receiving : 12 8PSK-3/5
    - current max : 14 8PSK-3/4
              : On
Pilot
Frame length : Shor
DVB S2 Mode : ACM
                 : Short
DVB S2 Stream type : MPEG-TS
                  : 0.20
Roll off
                  : 10.5 dB
SNR
Input Power
                  : -29 dBm
IP DVB 172.18.131.30/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
C:\Documents and Settings\Administrator.DVB-RCS>ping 172.18.131.29
Pinging 172.18.131.29 with 32 bytes of data:
Reply from 172.18.131.29: bytes=32 time=1835ms TTL=62
Reply from 172.18.131.29: bytes=32 time=913ms TTL=62
Reply from 172.18.131.29: bytes=32 time=552ms TTL=62
Reply from 172.18.131.29: bytes=32 time=1686ms TTL=62
Ping statistics for 172.18.131.29:
   Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 552ms, Maximum = 1835ms, Average = 1246ms
Ping desde dentro da VSAT 8.8.8.8
# 64 bytes from 8.8.8.8: time=550 ms
64 bytes from 8.8.8.8: time=1930 ms
64 bytes from 8.8.8.8: time=740 ms
64 bytes from 8.8.8.8: time=2590 ms
64 bytes from 8.8.8.8: time=830 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 550/1320/2590 ms
```