

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

Empresa VSAT-ID Link kbps Plataforma EMC Brasil VIVO-PER-26062276-PE 256k/128k **VSAT**

dvb tx show

Satellite (DVB) TX Configuration

Auto start Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.7 dBm EIRP : 48.0 dBW Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)

IDU Output Power : -23.6 dBm

ODU Output Power : 34.6 dBm : 47.9 dBW EIRP : 14.0 dB Es/No Header Compression : Disabled

Timing correction : -250 us (262255 us)

Frequency correction: -60 Hz

dvb rx show

Satellite (DVB) RX Configuration _____

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

9.320000 12.055825 DVB-S2 4 0 0.0 E * 0 0

Yes

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.056039 GHz

Symbol Rate : 9.319967 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 16 8PSK-8/9

: On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 C Roll off SNR : 13.9 dB

```
Input Power
            : -25 dBm
IP DVB 10.50.1.69/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=590 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=710 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 590/690/760 ms
```