

EMC Brasil

TERMO DE ACEITE TÉCNICO

VSAT

256K/128K

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: Vivo

Empresa

VSAT-ID

Link kbps

Plataforma

VIVO-PER-25059491-PB



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -18 dBm IDU Max Output Power: 0.0 dBm

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -17.8 dBm Es/No : 13.5 dB Header Compression : Disabled

Timing correction : -61 us (250091 us)

Frequency correction: 110 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								
1	1	25.333333	12.050000	DVB-S2	4	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

: On Rx State

DVB State : Forward link up : 1326, T14R Beam Network : 12.049931 GHz : 29.999897 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 22 16APSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS : 0.20 Roll off SNR : 15.8 dB Input Power : -35 dBm

