

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26075300-PE

Link kbps
256k/128k

Plataforma
VSAT



SatLink VSAT

10.29.57.33/www/dwp/index_page.dwp

STM SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model: SatLink 2000

Software Version: 16.0.1.57

LAN MAC Address: 00:20:0e:10:52:0b

DVB MAC Address: 00:20:0e:10:52:0b

System Up Time: 0 days, 00:23:22

CPU Load: 34%

System Name: VIVO-PER-26075300-PE

System Contact: Correntes - PE

System Location: Correntes - PE

ODU Serial Number: 104804040203080601400000

ODU HW Version: 4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

Telet 10.29.57.33

SW ID 128288, Revision 16.0.1 Build 59

Satellite (DVB) TX Configuration

Auto start: Enabled

IDU Output Power: -20 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power: max

EIRP: max

Default CM Frequency: 0.000000 GHz

RTM mode: UC-Max

Header Compression: None

Satellite (DVB) Transmitter Status

State: On (DVB-HCS2)

IDU Output Power: -14.3 dBm

ODU Output Power: 34.0 dBm

EIRP: 47.3 dBm

St-Me: 12.0 dB

Header Compression: Disabled

Timing correction: -84 us (251077 us)

Frequency correction: -110 Hz

Satellite (DVB) RX Configuration

Auto start: Enabled

Max Traffic M0BC00: 23

16APSK-9/10

RX watchdog: 15 minute

Idx	Pri	Enable	Substrate(MHz)	Freq(GHz)	Mode	Popid	SatId	Pos	SatName
0	0	Yes	25.333333	12.050000	DVB-S2 102		0	0.0 E	
1	1	Yes	15.000000	12.059000	DVB-S2 4		0	0.0 E	

Satellite (DVB) Receiver Status

Rx State: On

DVB State: Forward link up

Network: 1326, T148 Beam

Frequency: 12.049795 GHz

Symbol Rate: 25.333332 Msps

S2 ModCod: 20 16APSK-4/5

- receiving: 22 16APSK-8/9

Pilot: On

Frame length: Short

DVB S2 Mode: ACM

ODU S2 Stream type: MPEG-15

Roll off: 0.20

SNR: 15.2 dB

Input Power: -21 dBm

10:59 07/08/2017

SatLink VSAT

10.29.57.33/www/dwp/index_page.dwp

STM SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model: SatLink 2000

Software Version: 16.0.1.57

LAN MAC Address: 00:20:0e:10:52:0b

DVB MAC Address: 00:20:0e:10:52:0b

System Up Time: 0 days, 00:20:08

CPU Load: 29%

System Name: VIVO-PER-26075300-PE

System Contact: Correntes - PE

System Location: Correntes - PE

ODU Serial Number: 104804040203080601400000

ODU HW Version: 4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

C:\Windows\system32\cmd.exe

```

Resposta de 0.0.0.0: bytes=32 tempo=883ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=577ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=644ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=714ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=792ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=883ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=697ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=2540ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=666ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=731ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=604ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=677ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=638ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1367ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1886ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1800ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1648ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=2290ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=2007ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1760ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1331ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1513ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1820ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1521ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=911ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=2460ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=1560ms TTL=44
Resposta de 0.0.0.0: bytes=32 tempo=555ms TTL=44

Estatísticas do Ping para 0.0.0.0:
Pacotes: Enviados = 140, Recebidos = 140, Perdas = 0 GB de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 553ms, Máximo = 2540ms, Média = 1160ms
Control-C
C:\Users\DJformador>arp -a
'arp' não é reconhecido como um comando interno
ou externo, um programa operável ou um arquivo em lotes.
C:\Users\DJformador>arp -a

Interface: 10.29.57.34 --- 0x0
Endereço IP      Endereço físico      Tipo
10.29.57.33      00-20-0e-10-52-0b   dinâmico
224.0.0.22       01-00-5e-00-00-16   estático
224.0.0.251      01-00-5e-00-00-fb   estático
224.0.0.252      01-00-5e-00-00-fe   estático
224.0.1.68       01-00-5e-00-01-3c   estático
239.255.255.250  01-00-5e-7f-ff-fa   estático
255.255.255.255  ff-ff-ff-ff-ff-ff   estático
C:\Users\DJformador>

```

12:02 07/08/2017