


## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-31215139-MG256/128VSAT



# dvb tx show

Satellite (DVB) TX Configuration

-----

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.0000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -19.6 dBm

ODU Output Power : 34.0 dBm

EIRP : 47.3 dBW

Eb/No : 14.0 dB

Header Compression : Disabled

Timing correction : -151 us (262113 us)

Frequency correction: -240 Hz

```
# dvb rx show
Satellite (DVB) RX Configuration
_____
              : Enabled
: 23 16APSK-9/10 (SNR threshold: 23.5 dB)
Auto start
Max MODCOD
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes 1 1 0.000000 0.000000 DVB-S2 2 No
Satellite (DVB) Receiver Status
_____
Rx State
              : On
: Forward link up
: 1326, GlobalIP@Telstar-14R
: 12.055622 GHz
: 9.319878 Msps
                   : On
DVB State
Network
Frequency
Symbol Rate
S2 ModCod
     - receiving : 14 8PSK-3/4
     - current max : 23 16APSK-9/10
                  : On
Pilot
Frame length
                  : Short
DVB S2 Mode
                  : ACM
                   : 0.25
Roll off
                  : 14.7 dB
SNR
Input Power
                  : -27 dBm
IP DVB 10.53.0.192/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=890 ms
64 bytes from 8.8.8.8: time=740 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=710 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 700/1090/2440 ms
```