

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31084921-MG
 256/128
 VSAT



Satellite (DVB) RX Configuration

Auto start . Enables

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

ldx Pri SymbRate[Msps] Freq[GHz] Mode Popld SatId Pos SatName Name Enable

* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E Yes 9 9 15.000000 12.059000 DVB-S2 102 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up Network : 1326, T14R Beam Frequency : 12.055554 GHz Symbol Rate : 9.319896 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 21 16APSK-5/6

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS

Roll off : 0.20 SNR : 13.9 dB Input Power : -29 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -14.1 dBm
ODU Output Power : 33.5 dBm

EIRP : 46.8 dBW Es/No : 12.0 dB

Header Compression: Disabled

Timing correction : -242 us (260944 us)

Frequency correction: -110 Hz

ping 8.8.8.8 -n 10 -if 1

64 bytes from 8.8.8.8: time=1470 ms 64 bytes from 8.8.8.8: time=720 ms 64 bytes from 8.8.8.8: time=920 ms 64 bytes from 8.8.8.8: time=610 ms 64 bytes from 8.8.8.8: time=650 ms 64 bytes from 8.8.8.8: time=720 ms 64 bytes from 8.8.8.8: time=660 ms 64 bytes from 8.8.8.8: time=650 ms 64 bytes from 8.8.8.8: time=670 ms 64 bytes from 8.8.8.8: time=670 ms 64 bytes from 8.8.8.8: time=770 ms

--- ping statistics ---

10 packets transmitted, 10 received, 0.00 percent packet loss rtt min/avg/max = 610/780/1470 ms