

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-24074136-RN

Link kbps
256K/128K

Plataforma
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -18 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.7 dBm
EIRP                 : 47.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS2)
IDU Output Power     : -15.8 dBm
ODU Output Power     : 33.6 dBm
EIRP                 : 46.9 dBW
```

Es/No : 11.5 dB
Header Compression : Disabled
Timing correction : -25 us (250691 us)
Frequency correction: -160 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.049849 GHz
Symbol Rate : 25.332988 Msps
S2 ModCod
- receiving : 12 8PSK-3/5
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.5 dB
Input Power : -21 dBm

SatLink VSAT

10.29.61.193/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:56:96

00:20:0e:10:56:96

0 days, 00:01:55

15%

VIVO-PER-24074136-RN

GUAMARE-RN

104804040203090409860000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=556ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=756ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=828ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=907ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=722ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=765ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=845ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=657ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=738ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=812ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=852ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=581ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=661ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=745ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=828ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=891ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=689ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=685ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=752ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=830ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=902ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=616ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=708ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=783ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=858ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=597ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=659ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=738ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=828ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=904ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=610ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=670ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=735ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=824ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=896ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=620ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=694ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=774ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=872ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=573ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1227ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=706ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=797ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=761ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=597ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=642ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 57, Recebidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 556ms, Máximo = 1727ms, Média = 773ms
Control-C
^C
C:\Windows\System32>

19:29

28/08/2017