

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-231005062-CE 256/128 **VSAT**



Satellite (DVB) RX Configuration

: Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable

9.320000 * 0 0 12.055825 DVB-S2 4 Yes 0.000000 0.000000 DVB-S2 2 No 1 1

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

: 12.055757 GHz Frequency Symbol Rate : 9.319949 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

Pilot : On

: Short Frame length DVB S2 Mode : ACM Roll off : 0.25 SNR : 14.5 dB Input Power : -26 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.9 dBm

EIRP : 47.2 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -23.0 dBm
ODU Output Power : 33.8 dBm

EIRP : 47.1 dBW Eb/No : 14.0 dB

Header Compression: Disabled Timing correction: -221 us (260579 us)

Frequency correction: -310 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=690 ms 64 bytes from 8.8.8.8: time=530 ms 64 bytes from 8.8.8.8: time=580 ms 64 bytes from 8.8.8.8: time=520 ms 64 bytes from 8.8.8.8: time=540 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 520/570/690 ms