

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26106191-RN

Link kbps
256K/128K

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.0 dBm
EIRP                 : 46.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On   (DVB-RCS2)
IDU Output Power     : -20.3 dBm
ODU Output Power     : 33.0 dBm
```

EIRP : 46.0 dBW
Es/No : 11.0 dB
Header Compression : Disabled
Timing correction : -80 us (251492 us)
Frequency correction: -90 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
1	1	30.000000	12.050000	DVB-S2	4	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.049941 GHz
Symbol Rate : 25.332817 Msps
S2 ModCod
- receiving : 15 8PSK-5/6
- current max : 22 16APSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.9 dB
Input Power : -28 dBm

SatLink VSAT

10.29.64.249/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:5b:a6

00:20:0e:10:5b:a6

0 days, 00:08:14

24%

VIVO-PER-26106191-RN

ILHA DE ITAMARACA - PE

104804040203090703800000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=1369ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=910ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1150ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1691ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1088ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1914ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1439ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=716ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2094ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=635ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=574ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=729ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=869ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1440ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=700ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=574ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=729ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=694ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=890ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=718ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=797ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=741ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=831ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=630ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1074ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1325ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=601ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=709ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1944ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1194ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=835ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=917ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=759ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=833ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=795ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=621ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=825ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=666ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=751ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=829ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1032ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=709ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=893ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=613ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=688ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=763ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=617ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=615ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1057ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 57, Recebidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 574ms, Máximo = 2154ms, Média = 980ms
Control-C
^C
C:\Windows\System32>

11:07

09/09/2017