

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26062276-PE
 256k/128k
 VSAT



# dvb tx show

Satellite (DVB) TX Configuration

-----

Auto start : Enabled

IDU Output Power : -30 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 32.7 dBm

EIRP : 46.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS)
IDU Output Power : -17.5 dBm
ODU Output Power : 32.5 dBm
EIRP : 45.8 dBW
Es/No : 14.5 dB
Header Compression : Disabled

Timing correction : -128 us (262487 us)

```
Frequency correction: -340 Hz
## # dvb rx show
Satellite (DVB) RX Configuration
______
Auto start : Enabled
Max Traffic MODCOD : 28 32APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                                     Name
Enable
          9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
_____
Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.056165 GHz

Symbol Rate : 9.319922 Msps
S2 ModCod
    - receiving : 15 8PSK-5/6
      - current max : 15
                           8PSK-5/6
rilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type:
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 12.0 dB
Input Power : -25 dBm
IP DVB 172.18.131.147/32
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8 -if 1 -t
# 64 bytes from 8.8.8.8: time=1600 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=600 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=590 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=640 ms
```