

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá

Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-25153218-PB256/128VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -21 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.2 dBm

EIRP : 46.5 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -22.5 dBm
ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Es/No : 12.5 dB
Header Compression : Disabled

Timing correction : -111 us (262534 us)

Frequency correction: 30 Hz

```
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                              Name
Enable
         9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
           : On
: Forward link up
Rx State
             : 1326, GlobalIP@Telstar-14R
: 12.056154 GHz
: 9 310005
DVB State
Network
Frequency
Symbol Rate
S2 ModCod
  - receiving : 16 8PSK-8/9
     - current max : 16
                         8PSK-8/9
              : On
Pilot
Frame length : Short DVB S2 Mode : ACM
                  : ACM
DVB S2 Stream type : MPEG-TS
Roll off
                  : 0.20
                  : 13.6 dB
SNR
Input Power
                  : -19 dBm
IP DVB 10.50.1.134 /32
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=860 ms
64 bytes from 8.8.8.8: time=750 ms
64 bytes from 8.8.8.8: time=990 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=490 ms
--- ping statistics ---
5 packets transmitted, 3 received, 40.00 percent packet loss
rtt min/avg/max = 540/890/1290 ms
```



