


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23006129-CE
 256/128
 VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055631 GHz Symbol Rate : 9.319835 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short

DVB S2 Mode : ACM
Roll off : 0.25
SNR : 15.2 dB
Input Power : -26 dBm

No Such Command

```
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.9 dBm
                   : 47.2 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -19.7 dBm

ODU Output Power : 34.0 dBm
EIRP
                   : 47.3 dBW
Eb/No
                   : 10.5 dB
Header Compression : Disabled
Timing correction : -74 us (260462 us)
Frequency correction: -290 Hz
IP DVB 10.50.0.5/32
#ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=1260 ms
64 bytes from 8.8.8.8: time=1010 ms
64 bytes from 8.8.8.8: time=810 ms
64 bytes from 8.8.8.8: time=1300 ms
64 bytes from 8.8.8.8: time=710 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 710/1010/1300 ms
```