

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-31081167-MG

Link kbps
256K/128K

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```

Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.7 dBm
EIRP                 : 47.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
  
```

Satellite (DVB) Transmitter Status

```

State                : On (DVB-RCS2)
IDU Output Power     : -12.4 dBm
ODU Output Power     : 34.3 dBm
EIRP                 : 47.6 dBW
Es/No                : 13.0 dB
  
```

Header Compression : Disabled
Timing correction : 38 us (248857 us)
Frequency correction: 50 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								
1	1	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status


Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.049820 GHz
Symbol Rate : 30.000177 Msp/s
S2 ModCod
- receiving : 12 8PSK-3/5
- current max : 21 16APSK-5/6
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.2 dB

Input Power : -30 dBm

SatLink VSAT

10.29.65.137/wmi/dwp/index_page.dwp

Apps Sites Sugeridos uu4uç~x Device

 SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:55:64
DVB MAC Address	00:20:0e:10:55:64
System Up Time	0 days, 01:23:43
CPU Load	13%
System Name	VIVO-PER-31081167-MG
System Contact	
System Location	Monte Azul - MG
ODU Serial Number	104804040203090308900000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

Administrador: Prompt de Comando

Microsoft Windows [versão 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. Todos os direitos reservados.

C:\Users\Asus>ping 8.8.8.8 -t

Disparando 8.8.8.8 com 32 bytes de dados:
Resposta de 8.8.8.8: bytes=32 tempo=869ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=930ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1039ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1051ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1074ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1076ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1164ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=986ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1064ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1084ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1062ms TTL=49
Resposta de 8.8.8.8: bytes=32 tempo=1087ms TTL=49

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 12, Recebidos = 12, Perdidos = 0 (0% de perda).

Aproximar um número redondo de vezes em milissegundos:
Mínimo = 869ms, Máximo = 1164ms, Média = 1040ms

Control-C
^C

C:\Users\Asus>arp -a

Interface: 10.29.65.138 --- 0xc
Endereço IP Endereço físico Tipo
10.29.65.137 00-20-0e-10-55-64 dinâmico
10.29.65.143 ff-ff-ff-ff-ff-ff estático
224.0.0.2 01-00-5e-00-00-02 estático
224.0.0.22 01-00-5e-00-00-16 estático
224.0.0.251 01-00-5e-00-00-fb estático
224.0.0.252 01-00-5e-00-00-fc estático
239.255.255.250 01-00-5e-7f-ff-fa estático
255.255.255.255 ff-ff-ff-ff-ff-ff estático

C:\Users\Asus>

PT 12:52
14/12/2017