


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

> **Empresa** VSAT-ID Link kbps **Plataforma** VIVO-PER-23113154-CE **EMC Brasil** 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

PV watchdox : 15 minute

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

: On Rx State

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

: 12.055571 GHz : 9.319916 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

```
Pilot
                   : On
Frame length
                : Short
DVB S2 Mode
                  : ACM
                  : 0.25
Roll off
                  : 13.6 dB
SNR
                  : -25 dBm
Input Power
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                  : 47.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -20.8 dBm

ODU Output Power : 34.0 dBm
EIRP
                   : 47.3 dBW
Eb/No
                   : 12.5 dB
Header Compression : Disabled
Timing correction : -181 us (260817 us)
Frequency correction: -260 Hz
IP DVB 10.50.0.76/32
# ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=2330 ms
64 bytes from 8.8.8.8: time=630 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 540/940/2330 ms
```