

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho. Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-27000915-AL
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -22 dBm IDU Max Output Power: 0.0 dBm Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

: On (DVB-RCS2)
IDU Output Power : -21.8 dBm
Es/No
Headar Header Compression : Disabled

Timing correction : 22 us (255055 us)

Frequency correction: 160 Hz

dvb rx show

Satellite (DVB) RX Configuration Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status ______

Rx State : On

DVB State : Forward link up

1226 T14R Bear : 1326, T14R Beam Network : 12.059249 GHz : 15.000744 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9

Pilot : On Frame length : Shor DVB S2 Mode : ACM : Short DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 15.0 dB : -32 dBm Input Power

IP DVB 172.18.132.238 /32