



**NOC/Operador:** Wallace Teixeira


**Cliente: VIVO**

**Empresa**  
EMC Brasil

**VSAT-ID**  
VIVO-PER-23116196-CE

Link kbps  
256k/128k

## Plataforma VSAT



## Satellite (DVB) TX Configuration

```
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.7 dBm
EIRP                 : 47.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

```
# dvb rx show
```

## Satellite (DVB) RX Configuration

```
Auto start           : Enabled
Max Traffic MODCOD   : 23    16APSK-9/10
RX watchdog          : 15 minute
```


Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
-----	-----	----------------	-----------	------	-------	-------	-----	---------	------

\* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E  
Yes  
1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E  
Yes

SatLink VSAT

192.168.0.1/wmi/dwp/index\_page.dwp

Apps ★ Bookmarks Facebook Itaú - cartões Bradesco | Rede de A

 SatLink VSAT

Status  
Satellite  
Statistics  
Device  
DHCP  
Eventlog  
Configuration  
Satellite  
IP  
Static NAT  
Lineup  
Device  
Help  
Introduction  
Status  
Configuration

Continuous Wave Transmission

BUC

SatLink 403x (14.0-14.5 GHz)

CW Frequency 0.000000 GHz

EIRP max dBW

ODU Output Power 32.0 dBm

CW Off

Start Calibration CW On CW Off Apply

Receive Signal

☐ Audio

Rx SNR [dB]

0 5 10

14.3

You are logged in as install (2)

right 2006-2014 STM Group. All Rig

Prompt de Comando

Resposta de 8.8.8.8: bytes=32 tempo=1066ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=704ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=776ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1208ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=2872ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=2457ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1627ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=571ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1631ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1285ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1309ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=713ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=782ms TTL=44  
  
Estatísticas do Ping para 8.8.8.8:  
Pacotes: Enviados = 59, Recebidos = 59, Perdidos = 0 (0% de perda),  
Aproximar um número redondo de vezes em milissegundos:  
Mínimo = 555ms, Máximo = 2872ms, Média = 1239ms  
Control-C  
^C  
C:\Users\Arnaldo>arp -a  
  
Interface: 10.29.44.42 --- 0xd  
Endereço IP Endereço físico Tipo  
10.29.44.41 00-20-0e-10-4c-c2 dinâmico  
10.29.44.47 ff-ff-ff-ff-ff-ff estático  
224.0.0.2 01-00-5e-00-00-02 estático  
224.0.0.251 01-00-5e-00-00-fb estático  
224.0.0.252 01-00-5e-00-00-fc estático  
239.192.152.143 01-00-5e-40-98-8f estático  
239.255.255.250 01-00-5e-7f-ff-fa estático  
255.255.255.255 ff-ff-ff-ff-ff-ff estático  
  
C:\Users\Arnaldo>

terça-feira, 20 de junho de 2017

junho de 2017

D	S	T	Q	Q	S	S
28	29	30	31	1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	1
2	3	4	5	6	7	8

17:12:15

Alterar configurações de data e hora...

Sem título - Bloco de n...

Arquivo Editar Formatar Exibir

Ajuda

VIVO-PER-23116196-CE

You are logged in as install (2)

right 2006-2014 STM Group. All Rig

PT

17:12

20/06/2017