

# TERMO DE ACEITE TÉCNICO

Solicitante: IMAIS-NONA

NOC/Operador: Pedro Henrique da Rocha Bernardes Cliente: IMAIS-NONA

VSAT-ID Empresa Link kbps **Plataforma** EMC Brasil **IMAIS-NONA** 2M/512K **VSAT** 

## Satellite (DVB) RX Configuration

-----

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

\* 0 0 10.680000 12.164510 DVB-S2 103 0 0.0 E Yes

## Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, Anik G1 Beam

Frequency : 12.164986 GH-Frequency : 12.164986 GHz Symbol Rate : 10.679868 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 13 8PSK-2/3

Pilot : On Frame length : Short : ACM DVB S2 Mode

DVB S2 Stream type: MPEG-TS

Roll off : 0.25 SNR : 9.3 dB Input Power : -41 dBm

#### Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -13 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 35.0 dBm : 48.0 dBW EIRP

Default CW Frequency: 14.131100 GHz

ATM mode : VC-Mux Header Compression: None

#### Satellite (DVB) Transmitter Status

State : On (DVB-RCS) IDU Output Power : -9.5 dBm ODU Output Power : 34.7 dBm

: 47.7 dBW EIRP Es/No : 10.0 dB

Header Compression: Disabled

Timing correction: -274 us (269685 us)

Frequency correction: -1070 Hz

System Information:

: IMAIS-NONA Name

Location : AM

Contact

System Up time : 0 days, 00:33:55 CPU Load : 17%

System time(UTC) : 16 March 2017 13:58:39

Broadcast Message : not set

HW:

Model : SatLink 2000 HW ID : 120033

Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:5f:23 Satellite (DVB) : 00:20:0e:10:5f:23

Disparando 172.22.128.79 com 32 bytes de dados:

Resposta de 172.22.128.79: bytes=32 tempo=1839ms TTL=62 Resposta de 172.22.128.79: bytes=32 tempo=568ms TTL=62 Resposta de 172.22.128.79: bytes=32 tempo=1577ms TTL=62 Resposta de 172.22.128.79: bytes=32 tempo=945ms TTL=62

Estatísticas do Ping para 172.22.128.79:

Pacotes: Enviados = 4, Recebidos = 4, Perdidos = 0 (0% de perda),

Aproximar um número redondo de vezes em milissegundos: Mínimo = 568ms, Máximo = 1839ms, Média = 1232ms