

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26046105-PE

Link kbps
256/128

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -30 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 35.0 dBm
EIRP                 : 48.0 dBW
Default CW Frequency : 14.125850 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS)
IDU Output Power     : -21.7 dBm
ODU Output Power     : 35.7 dBm
EIRP                 : 48.7 dBW
Es/No                : 14.0 dB
Header Compression   : Disabled
Timing correction     : -176 us (261880 us)
Frequency correction : 10 Hz
```

#

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
* 0	0	9.320000	12.055825	DVB-S2	102	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055760 GHz
Symbol Rate : 9.320039 Msps
S2 ModCod
- receiving : 16 8PSK-8/9
- current max : 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.5 dB
Input Power : -20 dBm

#

IP DVB 172.28.131.22 /32

ping 8.8.8.8

64 bytes from 8.8.8.8: time=660 ms
64 bytes from 8.8.8.8: time=550 ms
64 bytes from 8.8.8.8: time=690 ms
64 bytes from 8.8.8.8: time=1020 ms
64 bytes from 8.8.8.8: time=620 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 550/700/1020 ms

#

