


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique

Cliente: VIVO

Empresa VSAT-ID Link kbps Plataforma
EMC Brasil VIVO-PER-26140306-PE 256k/128k VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm

ODU Output Power : max

EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2) IDU Output Power : -11.4 dBm

ODU Output Power : 34.1 dBm

EIRP : 47.4 dBW Es/No : 10.0 dB

Header Compression: Disabled

Timing correction : -46 us (254141 us)

Frequency correction: 100 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pı	ri SymbRate[Msps] Freq[GHz] Mode Po	opId SatId Pos	SatName	Name	Enable
* 0 0	15.000000	12.059000 DVB-S2 102	0 0.0 E		Yes	
1 1	9.320000	12.055825 DVB-S2 4	0 0.0 E		Yes	
6 6	25.333333	12.050000 DVB-S2 102	0 0.0 E		Yes	
7 7	30.000000	12.050000 DVB-S2 102	0 0.0 E		Yes	

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.058905 GHz
Symbol Rate : 15.000005 Msps

S2 ModCod

- receiving : 7 QPSK-3/4 - current max : 20 16APSK-4/5

Pilot : On Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.0 dB Input Power : -29 dBm

