

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-27008550-AL
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 14.169750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2) IDU Output Power : -15.3 dBm

ODU Output Power : 33.7 dBm EIRP : 47.0 dBW Es/No : 11.0 dB

Header Compression : Disabled

Timing correction : 9 us (249702 us)

Frequency correction: -30 Hz

dvb rx show

Satellite (DVB) RX Configuration -----Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
0	0	30.000000	12.050000	DVB-S2	102	0	0.0 E		
Yes									
1	1	25.333333	12.050000	DVB-S2	102	0	0.0 E		
No									
* 5	5	30.000000	11.592000	DVB-S2	102	0	0.0 E		
Yes									
6	6	25.333333	12.050000	DVB-S2	102	0	0.0 E		
Yes									
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E		
Yes									
9	9	25.333000	11.592000	DVB-S2	102	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 11.592344 GHz

Symbol Rate : 29.999914 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 21 16APSK-5/6

Pilot : On Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 15.4 dB Input Power : -23 dBm



