

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Silva Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-26140594-PE256/128VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.5 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -19.2 dBm
ODU Output Power : 34.2 dBm
EIRP : 47.7 dBW
Es/No : 14.0 dB
Header Compression : Disabled

Timing correction : -162 us (262496 us)

Frequency correction: -120 Hz

#

dvb rx show

Satellite (DVB) RX Configuration ______

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.055954 GHz

Symbol Rate : 9.320045 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 15 8PSK-5/6

: On Pilot Frame length : Short DVB S2 Mode : ACM : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 12.5 dB Input Power : -19 dBm

