



TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Ermínio Junior

Operadora/Cliente: Sergio Ramos

GRE/Prodemge: João Antinossi


Responsável/cliente: José Elias Neto

Consórcio
EMC/Vodanet

VSAT-ID
SEE-IBIA-22063

Porta kbps
2Mbps

Plataforma
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.2 dBm
EIRP                 : 46.5 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : UDP/IP
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS2)
IDU Output Power     : -16.4 dBm
ODU Output Power     : 33.0 dBm
EIRP                 : 46.3 dBW
Es/No                : 14.5 dB
Header Compression   : Disabled - HC for RCS2 not supported by HUB
Timing correction    : -305 us (281801 us)
Frequency correction  : 180 Hz
```

```
# dvb rx show
```

Satellite (DVB) RX Configuration

```
-----
Auto start           : Enabled
Max Traffic MODCOD   : 23   16APSK-9/10
RX watchdog          : 15 minute
```

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	4.883300	12.176420	DVB-S2	104	0	0.0 E	
Yes								
1	1	16.667000	11.962753	DVB-S2	2	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

```
-----
Rx State             : On
DVB State            : Forward link up
Network              : 65281, Prodemge@Vodanet
Frequency            : 12.176344 GHz
Symbol Rate          : 4.883025 Msps
S2 ModCod
- receiving          : 4   QPSK-1/2
- current max        : 21   16APSK-5/6
Pilot                : On
Frame length         : Short
DVB S2 Mode          : ACM
DVB S2 Stream type   : MPEG-TS
Roll off             : 0.20
SNR                  : 14.2 dB
Input Power          : -35 dBm
```

```
# device show
```

System Information:

```
Name           : SEE-IBAI-22063
Location        : IBIA - MG
Contact         :
System Up time  : 0 days, 01:10:43
CPU Load        : 25%
System time(UTC): 11 October 2017 19:09:48
Broadcast Message : not set
```

HW:

```
Model           : SatLink 2000
HW ID           : 120033
Main board ID    : 120026 R6.2
```

MAC addresses:

```
Ethernet (LAN)   : 00:20:0e:10:55:37
Satellite (DVB)  : 00:20:0e:10:55:37
```

```
# arp show
```

NetAddr	State	MacAddr	If
10.212.135.2	Dynamic	74:e6:e2:d4:e4:73	1

```
Reply from 10.212.135.1: bytes=32 time=720ms TTL=56
Reply from 10.212.135.1: bytes=32 time=571ms TTL=56
Reply from 10.212.135.1: bytes=32 time=570ms TTL=56
Reply from 10.212.135.1: bytes=32 time=604ms TTL=56
Reply from 10.212.135.1: bytes=32 time=580ms TTL=56
Reply from 10.212.135.1: bytes=32 time=594ms TTL=56
Reply from 10.212.135.1: bytes=32 time=559ms TTL=56
Reply from 10.212.135.1: bytes=32 time=579ms TTL=56
```

Reply from 10.212.135.1: bytes=32 time=542ms TTL=56
Reply from 10.212.135.1: bytes=32 time=576ms TTL=56

Ping statistics for 10.212.135.1:

Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 542ms, Maximum = 720ms, Average = 589ms

Lista de sites acessados:

www.globo.com – ok

www.hotmail.com – ok

www.google.com – ok

www.educacao.mg.gov.br – ok

www.prodemge.gov.br-ok

Responsável pelo teste de navegação:

Nome: José Elias Neto

Função: Coordenador

Identidade: MG10622039

Funcionamento: 07:00 até 16:15