

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho.

Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-23127945-CE256k/128kVSAT



dvb tx show

Satellite (DVB) TX Configuration

Took a struct

Auto start : Enabled
IDU Output Power : -18 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -17.9 dBm
Es/No : 14.5 dB
Header Compression : Disabled

Timing correction : -111 us (254526 us)

Frequency correction: -10 Hz

dvb rx show

Satellite (DVB) RX Configuration -----

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.059132 GHz

Symbol Rate : 15.000274 Msps

S2 ModCod

- receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off Roll off : 0.20 : 15.1 dB SNR Input Power : -34 dBm

IP DVB 172.18.132.126 /32