



## TERMO DE ACEITE TÉCNICO

**Solicitante:** ATI - Agência de Tecnologia da Informação do Estado do Piauí

**NOC/Operadora:** Wallace Teixeira

**Técnico Instalador:** Claudinei Costa

**Contato:** 11 97701-2709

**Email:** claudnei@telecomtorre.com.br

**Responsável/cliente:** Ivaldo Carvalho Silva

**Orgão:** SEDUC

**Unidade:** Escolar Leda Napoleão

**Data Instalação**

06/10/2018

**Data Ativação**

06/10/2018

**Operadora**  
Global Eagle

**VSAT-ID**  
ATI-ES-0115-IND

**Porta kbps**  
4096/512

**Tipo**  
Indoor

Piauí, 06 de Outubro de 2018

1 – Local da Instalação



## 2 – Configurações do Modem

device show

System Information:

Name : ATI-ES-0115-IND  
Location : PI  
Contact :  
System Up time : 1 day, 06:03:06  
CPU Load : 8%  
System time(UTC) : 16 October 2018 06:10:34  
Broadcast Message : not set

HW:

Model : SatLink 2000  
HW ID : 120033  
Main board ID : 120026 R6.2

MAC addresses:

LAN : 00:20:0e:10:86:82  
Satellite (DVB) : 00:20:0e:10:86:82

# dvb tx show

Satellite (DVB) TX Configuration

-----  
Auto start : Enabled  
BUPC status : Disabled  
IDU Output Power : -19 dBm  
IDU Max Output Power: 0.0 dBm  
Default CW Frequency: 0.000000 GHz  
ATM mode : VC-Mux  
Header Compression : None

Satellite (DVB) Transmitter Status

-----  
State : On (DVB-RCS2)  
IDU Output Power : -18.9 dBm  
Es/No : 12.0 dB  
Header Compression : Disabled  
Timing correction : -97 us (249858 us)  
Frequency correction: 50 Hz

# dvb rx show

Satellite (DVB) RX Configuration

-----  
Auto start : Enabled  
Max Signalling MODCOD : 23 16APSK-9/10  
Max Traffic MODCOD : 28 32APSK-9/10  
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	25.000000	11.628079	DVB-S2	105	0	0.0 E		Yes	

Satellite (DVB) Receiver Status



IP	Receive	Deliver	Errors	InDiscards	Forward	Request	NoRoute	OutDiscards
63041	7918	0	0	58855	9266	0	61	

## Interface Directed Routing Table

In If Out If

### -----IP LAC Statistics-----

RPF	Src eq dest	RPF HitCount	Src eq dest HitCount	MfcHitCount (-1/drop classified)
Disabled	Enabled	0	0	0

## Routing Table

DestMask	RouteMask	NextHop	If	RtType	Row-Status
0.0.0.0	0.0.0.0	0.0.0.0	3	STATIC	ACTIVE
10.225.1.172	255.255.255.252	0.0.0.0	1	LOCAL	ACTIVE
10.225.117.0	255.255.255.0	10.225.1.174	1	STATIC	ACTIVE
172.18.192.124	255.255.255.255	0.0.0.0	3	LOCAL	ACTIVE

## 3 – Configurações dos Equipamentos



4 – Teste de Velocidade

Download/Uplond

