

# TERMO DE ACEITE TÉCNICO

**Solicitante:** VIVO- Projeto Escolas Rurais

**NOC/Operador:** Wallace Teixeira

**Cliente:** VIVO

**Empresa**  
EMC Brasil

**VSAT-ID**  
VIVO-PER-28000404-SE

**Link kbps**  
256k/128k

**Plataforma**  
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 32.7 dBm
EIRP                 : 46.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```


Satellite (DVB) Transmitter Status

```
-----
State                : On   (DVB-RCS2)
```

IDU Output Power : -17.8 dBm  
ODU Output Power : 32.6 dBm  
EIRP : 45.9 dBW  
Es/No : 13.5 dB  
Header Compression : Disabled  
Timing correction : -19 us (250818 us)  
Frequency correction: -20 Hz

SatLink VSAT

10.29.55.201/term/dhcp/index\_page.php

 SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Unsup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2050
Software Version	16.0.1.57
LAN MAC Address	00 20 0e 10 4f 2a
DVB MAC Address	00 20 0e 10 4f 2a
System Up Time	0 days, 00:19:35
CPU Load	21%
System Name	VIVO-PER-26000404-SE
System Contact	
System Location	Sera nova-SE
ODU Serial Number	104804040203090503710000
ODU HW Version	4.2

You are logged in as install (X)

© Copyright 2006-2014 STM Group. All Rights Reserved.

C:\Windows\system32\cmd.exe

Resposta de 8.8.8.8: bytes=32 tempo=229ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=218ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=145ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=718ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=779ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=713ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=802ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=874ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=867ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=603ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=811ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=867ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1436ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=955ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1387ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=2158ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1482ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1684ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1874ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1518ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=615ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1064ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1064ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1798ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1813ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1437ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1433ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1769ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1891ms TTL=44  
Resposta de 8.8.8.8: bytes=32 tempo=1804ms TTL=44  
  
Estatísticas de Ping para 8.8.8.8:  
Fontes: Enviados = 87, Recebidos = 87, Perdidos = 0 CBx de perda).  
Aproximar um número redondo de vezes em milissegundos:  
Mínimo = 556ms, Máximo = 2426ms, Média = 1021ms  
Control-C  
C:\Monar>ipconfig /all  
  
Interface: 10.29.55.202 --- Bch  
Endereço IP: Endereço Físico Tipo  
10.29.55.201 00-20-0e-10-4f-2a dinâmico  
10.29.55.207 ff-ff-ff-ff-ff-ff estático  
224.0.0.2 01-00-5e-00-00-02 estático  
224.0.0.22 01-00-5e-00-00-16 estático  
224.0.0.251 01-00-5e-00-00-fb estático  
224.0.0.252 01-00-5e-00-00-fc estático  
224.0.1.60 01-00-5e-00-01-3c estático  
239.255.255.250 01-00-5e-7f-ff-fa estático  
255.255.255.255 ff-ff-ff-ff-ff-ff estático  
  
C:\Monar>ipconfig /all