


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil 256/128 **VSAT** VIVO-PER-26073862-PE



Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName

Name Enable

9.320000 12.055825 DVB-S2 102 * 0 0 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

: 12.056077 GHz Frequency Symbol Rate : 9.320214 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 16 8PSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.4 dB Input Power : -30 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -23 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -23.5 dBm
ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW Es/No : 14.0 dB

Header Compression: Disabled

Timing correction : -147 us (262056 us)

Frequency correction: -60 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=760 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=730 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 710/720/760 ms