


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-22020292-PI
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -30 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -19.3 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Es/No : 16.0 dB
Header Compression : Disabled

Timing correction : -146 us (259746 us)

Frequency correction: -120 Hz

dvb rx show

Satellite (DVB) RX Configuration

: Enabled Auto start

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status _____

Rx State : On

: Forward link up : 1326, T14R Beam DVB State Network : 12.055650 GHz Frequency Symbol Rate

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 15 8PSK-5/6

: On Pilot : Short Frame length DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 11.6 dB : -30 dBm Input Power

